

UV-UHO-P2S-M33F34

Uniarch



Features

- Uniarch
- Panda P Series
- PT WIFI IP Camera
- **Double lens:** Integration of a fixed lens camera for general situation observation and a PT camera for tracking or focusing on other off-scene details
- **Lente panorámica de 2.8 mm con sensor de 1/2.8" y resolución 3MP (2304*1296)@25/20fps**
- **Lente PT de 4mm con sensor de 1/2.8" y resolución 3MP (2304*1296)@25/20fps**
- Ultra 265, H.265, H.264
- Supports digital WDR
- Built-in microphone and speaker, supports two-way audio, provides better interaction
- Supports deterrent sound and light, makes deterrence more noticeable in case of alarm
- Supports automatic tracking (Autotracking)
- Human and vehicle detection
- IR night vision, up to 30 m IR distance
- White light, up to 30 m white light distance
- Supports dual light mode: Changes between infrared and white light automatically when preset is activated.
- Supports 512 Micro SD card of [%VAR%] GB
- Wi-Fi connection and easy installation
- Suitable for exterior IP66

Specifications

Brand	Uniarch
Image sensor	1/2.8" Progressive Scan CMOS
Maximum resolution	3 Megapixel (2304x1296)
Fixed lens	2.8 mm
PT Lens	4.0 mm
Main Stream rate	Panoramic / PT: 3MP (2304x1296)@15fps; 2MP (1920x1080)@15fps; 720P (1280x720)@15fps
Extra Stream rate	Panoramic / PT: 640x360@15fps; 2CIF (704x288)@15fps; CIF (352x288)@15fps
Video compression	Ultra 265, H.265, H.264, MJPEG
Minimum illumination	Colour: 0.003 lux (F1.6 AGC ON) 0 lux with IR on
Infrared range	Overview: 30 m PT: 30 m
Detection functions	Motion Detection, Ultra Motion Detection, Audio Detection, Tamper Alarm.
Image improvements	DWDR, BLC, HLC, AGC, 2D/3D-NR, Motion detection, ROI, Privacy Mask
Day / Night	Mechanical ICR filter
Internal memory	MicroSD card, Max 512 GB
Alarms	Does not have
Audio	Built-in microphone and speaker
Audio Compression	G.711U, G.711A
Wi-Fi	IEEE802.11b/g/n/ax
Wi-Fi frequency range	2.4 GHz ~ 2.4835 GHz
Autotracking	Support
Remote access	Web Browser, CMS Software (EZStation), Smartphone (UNV-LINK, UNV-LINK Pro, Uniarch APP)
Power	DC 12V / 10W
Temp. operation	-30° C ~ 60° C
Degree of protection	Waterproof IP66, overvoltage 4KV

Dimensions

Ø117(W) x 117(D) x 202(H) mm

Weight

610 g