

UV-UHO-P3C-M5F4

Uniarch



Features

- PT IP Camera - Uniarch range
- 5 MP (2880x1620)
- 4 mm Lens
- Minimum illumination 0.0003 lux | 0 Lux with supplemental lighting
- White light range 30m
- ColorHunter with Wise-ISP technology:
- Active Dissolution: this camera is equipped with an alarm light and siren to alert when intruders are detected
- Wifi
- Built-in microphone
- Built-in speaker
- DWDR
- Slot for microSD up to 512 GB
- 20 Presets
- IP66

Specifications

Brand	Uniarch
Image sensor	1/1.8" Progressive Scan CMOS
Maximum resolution	5 Megapixel (2880x1620)
Lens	4 mm
Viewing angle	89.4° (H), 48.2° (V), 97.7° (D)
Range performance	62.1 m (D), 24.8 m(O), 12.4 m (R), 6.2 m (I)
Main Stream rate	5MP (2880x1620)@25fps; 4MP (2560x1440)@25fps; 3MP (2304x1296)@30fps; 2MP (1920x1080)@30fps; 720P (1280x720)@30fps
Extra Stream rate	640x360@30fps; 2CIF (704x288)@30fps; CIF (352x288)@30fps
Compression	Ultra 265, H.265, H.264, MJPEG
Minimum illumination	Colour: 0.0003Lux (F1.0, AGC ON)
White light range	30 m
Detection functions	Motion Detection, Human Detection, Audio Detection
Image improvements	DWDR, BLC, HLC, AGC, 2D/3D-NR, Motion detection, ROI, Privacy Mask
Internal memory	MicroSD card, Max 512 GB
Alarms	Does not have
Audio Compression	G.711U; G.711A
Audio	Built-in microphone and speaker
Bit rate	128 Kbps ~ 6144 Kbps
Wi-Fi	IEEE802.11b/g/n/ax
WI-FI frequency range	2.4 GHz ~ 2.4835 GHz
Remote access	Web Browser, CMS Software (EZStation), Smartphone (UNV-LINK, UNV-LINK Pro, Uniarch APP)
Power	DC 12V / 10W
Temp. operation	-30° C ~ 60° C
Degree of protection	Weatherproof IP66

Dimensions

Ø118 x 118 x 199 mm

Weight

530 g
