

Analogue CCTV / XVRs

# iDS-7208HUHI-M1/XT/8A+8/4ALM

HIKVISION



## Features

---

- Hikvision
- VALUE range
- DVR 5n1
- 8 CH video HDTV/HD/HD/HD/HD / 16 IP
- H.265 Pro+/H.265 Pro/H.265/H.264+/H.264
- Maximum input resolution 8MP @12fps
- Motion detection on all channels
- AcuSense, false alarm filter for vehicles and persons in up to 8 channels
- Face detection up to 4 channels
- Facial recognition
- Audio input and output
- Audio over coaxial
- Alarms
- Control PTZ (RS485, Coaxial)
- HDMI 4K, VGA & CVBS Outputs
- Space for 1 HDD

## Specifications

---

<b>Brand</b>	HIKVISION
<b>Range</b>	VALUE
<b>Video format</b>	HDTVI / HDCVI / AHD / CVBS / IP
<b>Video inputs</b>	8 Channels BNC, (HDTVI / HDCVI / AHD / CVBS)
<b>Hybrid configuration</b>	8 Additional IP CH: Up to 16 IP channels (8 Mpx), replacing all BNC channels
<b>Video outputs</b>	1 HDMI 4K and 1 VGA, simultaneous; 1 BNC CVBS
<b>Display resolution</b>	HDMI: 4K (3840x2160), 2K (2560x1440), 1920x1080, 1280x1024, 1280x720 / 60Hz VGA: 1920x1080, 1280x1024, 1280x720 / 60Hz CVBS: 704x576 (PAL) / 704x480 (NTSC)
<b>Audio inputs</b>	1 Channel RCA 8 coaxial audio channels
<b>Audio outputs</b>	1 Channel RCA
<b>Bidirectional audio</b>	Reusing the audio input
<b>Audio Bit Rate</b>	64 Kbps
<b>Audio compression</b>	G.711u
<b>Video compression</b>	H.265 Pro+ / H.265 Pro / H.265 / H.264+ / H.264
<b>Input resolution</b>	HDTVI: 8Mpx @ 12FPS, 3K (2960x1665)@25FPS, 5Mpx @20FPS, 4Mpx @25FPS, 1080p@25FPS, 720p@25FPS HDCVI: 8Mpx @ 12FPS, 3K (2880x1620)@25FPS, 5Mpx @20FPS, 4Mpx @25FPS, 1080p@25FPS, 720p@25FPS AHD: 5Mpx @20FPS, 4Mpx @25FPS, 1080p@25FPS, 720p@25FPS
<b>Main Stream coding</b>	8Mpx@8 FPS; 3K@12 FPS, 5Mpx@12 FPS; 4Mpx @15 FPS; 8Mpx Lite@15 FPS; 3Mpx@18 FPS; 1080p /720p/WD1/4CIF/VGA/CIF@25 FPS(P)
<b>Extra Stream coding</b>	WD1 / 4CIF / CIF (25 FPS)
<b>Video Bit Rate</b>	32 Kbps at 10 Mbps
<b>Simultaneous multifunction</b>	Pentaplex: Live, Recording, Playback, Backup and Remote Access
<b>Motion Detection</b>	Motion detection is available on all analog channels
<b>AcuSense</b>	AcuSense: Perimeter protection based on VCA rules with false alarm filter for human and vehicle detection applied on: Line Crossing, Area Intrusion. Available in up to 8 analog video channels.
<b>AcuSearch</b>	AcuSearch smart search up to 8 channels

<b>Facial Detection</b>	Facial recognition; photo search. Available in up to 4 channels.
<b>Facial recognition</b>	Up to 16 facial image libraries. A hard drive failure will not result in the loss of data from the facial image library, as it is backed up both on the hard drive and on flash memory. Facial image comparison alert from 4 channels (high-definition analog camera)
<b>Alarms</b>	8 inputs / 4 outputs
<b>Recording method</b>	Manual, programmed, motion detection
<b>Internal memory</b>	1 SATA HDD 3.5" of up to 12 TB (not included)
<b>Communication</b>	2 x USB 3.0 (rear panel) / 1 x USB 2.0 (front panel) / RS-485 / RJ45 (Ethernet)
<b>Bandwidth</b>	256 Mbps
<b>Remote connections</b>	64
<b>Remote access</b>	Web Browser, Hik-Connect Smartphone App, PC Software iVMS-4200 and Hik-Central
<b>Power</b>	DC 12 V, 2 A, ? 24 W (no HDD)
<b>Operating temperature</b>	-10° ~ +55° C
<b>Dimensions</b>	320 (W) x 240 (D) x 48 (H) mm
<b>Weight</b>	? 2 Kg (without HDD)